



WMX7406

**WiFi 6/6e 802.11ax 4x4 MU-MIMO
5-6GHz Wide Band Module**

Product Datasheet

Version: 0.1.0

2022/4/7



Release Note

[illegible]

Contents

1	Overview	1
2	Feature	1
2.1	General	1
2.2	WLAN	1
2.3	Security	1
3	System Specification	2
3.1	Block Diagram	2
3.2	Chip Solution	2
3.3	Protocol & Interface	2
3.4	Temperature	2
3.5	Humidity	2
4	WLAN Specification	3
4.1	WLAN Standard	3
4.2	Frequency Range	3
4.3	Band Width	3
4.4	Data Rate	3
4.5	Modulation	3
4.6	Output Power & Sensitivity (TBD)	4
5	Mechanical Specification	8
5.1	Mechanical Outline Drawing(TBD)	8
5.2	Dimension	8
5.3	Pin Assignment	9
5.4	Product Picture	10
5.5	Label Define	10
6	Electrical characteristics	10
6.1	Power Consumption	10
6.2	Operating Voltage	10
7	Software & Driver	11
7.1	Driver Support	11
7.2	Platform Support List	11
7.3	RF Tool	11
8	Certification	11
9	Package	11
10	Ordering Information	12
10.1	Main Parts	12

10.2	Accessories (TBD)	12
------	-------------------------	----

EmWicon Preliminary
EmWicon Confidential

1 Overview

The WMX7406 enterprise module is a highly integrated wireless local area network (WLAN) mini PCIe module, the module based-on Qualcomm QCN9074 and that is an 802.11ax Wi-Fi 6/6e PCIe radio for Enterprise Access Points and Campus deployments.

2 Feature

2.1 General

- 5-6 GHz wide band support
- 4x4/160 MHz 11ax PCIe Radio

2.2 WLAN


- Dual-synthesizer WLAN radio up to 160MHz bandwidth support
- Supports up to 512 simultaneously connected clients
- MU-MIMO for 802.11ac/ax and MU-OFDMA for 802.11ax
- Dynamic frequency selection (DFS)
- Supports up to 4096 QAM in all antenna and BW configurations, except for 4x4/160 that supports 1024 QAM
- Spatial reuse through BSS color, OBSS-PD, SRG and SRP
- Dynamic bandwidth switching
- Locationing (RSSI and RTT-based, 802.11REVmc compliant)
- Supports monitor mode

2.3 Security

- AES-CCMP at 128/256 bits
- AES-GCMP at 128/256 bits
- WEP, TKIP hardware encryption
- WAPI-2 hardware encryption
- WPA/WPA2-Personal/WPA2-Enterprise and WPA3 Personal
- FIPS ECB

3 System Specification

3.1 Block Diagram



3.2 Chip Solution

- Qualcomm QCN9074

3.3 Protocol & Interface

- PCIe Gen 3 interface for mini PCIe
- Antenna Port: U.FL connector x4 for 4T4R

3.4 Temperature

- Operating Temperature: -20°C to +70°C (TBD)
- Operating Temperature: -40°C to +85°C (I-Grade, TBD)
- Storage Temperature: -40°C to +105°C

3.5 Humidity

- Operating Humidity (non-condensing): 5% ~ 95%
- Storage Humidity (non-condensing): 5% ~ 90%

4 WLAN Specification

4.1 WLAN Standard

- IEEE 802.11a/n/ac/ax
- IEEE 802.11d, h, i, j, k, r, u, v, w and x

4.2 Frequency Range

- Support full 5-6GHz frequency range: 4900MHz -7125MHz

4.3 Band Width

- Supports 5/10 MHz in 4.9 GHz (Public Safety band)
- Supports 20/40/80/160 MHz in 5 GHz and 6GHz

4.4 Data Rate

- 5/6 GHz bands, the maximum PHY rate of 4804 Mbps is achieved in 802.11ax 4x4/160 MHz native operation.
- Maximum data rates of band-width
20MHz: 143Mbps for 1x1, 573Mbps for 4x4
40MHz: 287Mbps for 1x1, 1147Mbps for 4x4
80MHz: 600Mbps for 1x1, 2402Mbps for 4x4
160MHz: 1201Mbps for 1x1, 4804Mbps for 4x4

4.5 Modulation

- 802.11n:
OFDM (BPSK, QPSK, 16-QAM, 64-QAM)
- 802.11ac:
OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM)
- 802.11ax:
OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM)

4.6 Output Power & Sensitivity (TBD)

802.11a			
Data Rate	Tx $\pm$ 2dB	Tx $\pm$ 2dB(4TX)	Rx Sensitivity $\pm$ 2dB
6Mbps	19dBm	25dBm	-94dBm
24Mbps	18dBm	24dBm	-91dBm
54Mbps	18dBm	24dBm	-90dBm

802.11ac				
Data Rate		Tx $\pm$ 2dB	Tx $\pm$ 2dB(4TX)	Rx Sensitivity $\pm$ 2dB
VHT20	MCS 0	18dBm	24dBm	-94dBm
	MCS 1	18dBm	24dBm	-91dBm
	MCS 2	18dBm	24dBm	-90dBm
	MCS 3	18dBm	24dBm	-86dBm
	MCS 4	18dBm	24dBm	-83dBm
	MCS 5	16dBm	22dBm	-80dBm
	MCS 6	16dBm	22dBm	-77dBm
	MCS 7	15dBm	21dBm	-75dBm
	MCS 8	14dBm	20dBm	-71dBm
VHT40	MCS 0	18dBm	24dBm	-91dBm
	MCS 1	18dBm	24dBm	-88dBm
	MCS 2	18dBm	24dBm	-85dBm
	MCS 3	18dBm	24dBm	-82dBm
	MCS 4	18dBm	24dBm	-79dBm
	MCS 5	16dBm	22dBm	-75dBm
	MCS 6	16dBm	22dBm	-73dBm
	MCS 7	15dBm	21dBm	-72dBm
	MCS 8	14dBm	20dBm	-69dBm
	MCS 9	13dBm	19dBm	-66dBm

VHT80	MCS 0	18dBm	24dBm	-91dBm
	MCS 1	18dBm	24dBm	-88dBm
	MCS 2	18dBm	24dBm	-85dBm
	MCS 3	18dBm	24dBm	-82dBm
	MCS 4	18dBm	24dBm	-79dBm
	MCS 5	16dBm	22dBm	-75dBm
	MCS 6	16dBm	22dBm	-73dBm
	MCS 7	15dBm	21dBm	-72dBm
	MCS 8	14dBm	20dBm	-69dBm
	MCS 9	13dBm	19dBm	-66dBm
VHT160	MCS 0	18dBm	24dBm	-91dBm
	MCS 1	18dBm	24dBm	-88dBm
	MCS 2	18dBm	24dBm	-85dBm
	MCS 3	18dBm	24dBm	-82dBm
	MCS 4	18dBm	24dBm	-79dBm
	MCS 5	16dBm	22dBm	-75dBm
	MCS 6	16dBm	22dBm	-73dBm
	MCS 7	15dBm	21dBm	-72dBm
	MCS 8	14dBm	20dBm	-69dBm
	MCS 9	13dBm	19dBm	-66dBm


802.11ax				
Data Rate		Tx $\pm$ 2dB	Tx $\pm$ 2dB(4TX)	Rx Sensitivity $\pm$ 2dB
HE20	MCS 0	18dBm	24dBm	-94dBm
	MCS 1	18dBm	24dBm	-91dBm
	MCS 2	18dBm	24dBm	-90dBm
	MCS 3	18dBm	24dBm	-86dBm
	MCS 4	18dBm	24dBm	-83dBm
	MCS 5	16dBm	22dBm	-80dBm
	MCS 6	16dBm	22dBm	-77dBm
	MCS 7	15dBm	21dBm	-75dBm
	MCS 8	14dBm	20dBm	-71dBm
	MCS 9	13dBm	19dBm	-71dBm
	MCS 10	13dBm	19dBm	-71dBm
	MCS 11	11dBm	17dBm	-71dBm

HE40	MCS 0	18dBm	24dBm	-91dBm
	MCS 1	18dBm	24dBm	-88dBm
	MCS 2	18dBm	24dBm	-85dBm
	MCS 3	18dBm	24dBm	-82dBm
	MCS 4	18dBm	24dBm	-79dBm
	MCS 5	16dBm	22dBm	-75dBm
	MCS 6	16dBm	22dBm	-73dBm
	MCS 7	15dBm	21dBm	-72dBm
	MCS 8	14dBm	20dBm	-69dBm
	MCS 9	13dBm	19dBm	-66dBm
	MCS 10	13dBm	19dBm	-66dBm
	MCS 11	11dBm	17dBm	-66dBm
	MCS 12	10dBm	16dBm	-66dBm
	MCS 13	10dBm	16dBm	-66dBm
HE80	MCS 0	18dBm	24dBm	-91dBm
	MCS 1	18dBm	24dBm	-88dBm
	MCS 2	18dBm	24dBm	-85dBm
	MCS 3	18dBm	24dBm	-82dBm
	MCS 4	18dBm	24dBm	-79dBm
	MCS 5	16dBm	22dBm	-75dBm
	MCS 6	16dBm	22dBm	-73dBm
	MCS 7	15dBm	21dBm	-72dBm
	MCS 8	14dBm	20dBm	-69dBm
	MCS 9	13dBm	19dBm	-66dBm
	MCS 10	13dBm	19dBm	-66dBm
	MCS 11	11dBm	17dBm	-66dBm
	MCS 12	10dBm	16dBm	-66dBm
	MCS 13	10dBm	16dBm	-66dBm

HE160	MCS 0	18dBm	24dBm	-91dBm
	MCS 1	18dBm	24dBm	-88dBm
	MCS 2	18dBm	24dBm	-85dBm
	MCS 3	18dBm	24dBm	-82dBm
	MCS 4	18dBm	24dBm	-79dBm
	MCS 5	16dBm	22dBm	-75dBm
	MCS 6	16dBm	22dBm	-73dBm
	MCS 7	15dBm	21dBm	-72dBm
	MCS 8	14dBm	20dBm	-69dBm
	MCS 9	13dBm	19dBm	-66dBm
	MCS 10	13dBm	19dBm	-66dBm
	MCS 11	11dBm	17dBm	-66dBm
	MCS 12	10dBm	16dBm	-66dBm
	MCS 13	10dBm	16dBm	-66dBm

5 Mechanical Specification

5.1 Mechanical Outline Drawing(TBD)




General tolerance: $\pm 0.2\text{mm}$

5.2 Dimension

- Mini PCIe full size
- Typical Dimension (TBD): (W)31.85mm x (L)50.80mm x (H)12.84mm

5.3 Pin Assignment



PIN #	Pin Name	Design Status	PIN #	Pin Name	Design Status
1	WAKE#	PCIE_WAKE	2	+3.3Vaux	3V3
3	COEX1	NC	4	GND	GND
5	COEX2	NC	6	+1.5V	NC
7	CLKREQ#	PCIE_CLKREQ	8	UIM_PWR	NC
9	GND	GND	10	UIM_DATA	NC
11	REFCLK-	PCIE_REFCLKN	12	UIM_CLK	NC
13	REFCLK+	PCIE_REFCLKP	14	UIM_RESET	NC
15	GND	GND	16	UIM_VPP	NC

17	Reserved	NC	18	GND	GND
19	Reserved	NC	20	W_DISABLE#	NC
21	GND	GND	22	PERST#	PCIE_RST
23	PERn0	PCIE_RXN	24	+3.3Vaux	3V3
25	PERp0	PCIE_RXP	26	GND	GND
27	GND	GND	28	+1.5V	NC
29	GND	GND	30	SMB_CLK	NC
31	PETn0	PCIE_TXN	32	SMB_DATA	NC
33	PETp0	PCIE_TXP	34	GND	GND
35	GND	GND	36	USB_D-	NC
37	Reserved	GND	38	USB_D+	NC
39	+3.3Vaux	3V3	40	GND	GND
41	+3.3Vaux	3V3	42	LED_WWAN	NC
43	GND	GND	44	LED_WLAN	PCIE_LED
45	RESERVED	NC	46	LED_WPAN	NC
47	RESERVED	NC	48	+1.5V	NC
49	RESERVED	NC	50	GND	GND
51	RESERVED	NC	52	+3.3Vaux	3V3

5.4 Product Picture

TBD

5.5 Label Define

TBD

6 Electrical characteristics

6.1 Power Consumption

- Max power consumption 11W (25°C) (TBD)

6.2 Operating Voltage

- Mini PCIe 3.3V

7 Software & Driver

7.1 Driver Support

- Qualcomm platform with QSDK
- Open driver ATH11K

7.2 Platform Support List

- IPQ8074 (Verified)
- IPQ6018 (Verified)
- (TBD)

7.3 RF Tool

- RF test tool consultant service available

8 Certification

TBD

9 Package

TBD

10 Ordering Information

10.1 Main Parts

Part Number	Description
WMX7406	802.11ax, 4x4, 5G, Enterprise WiFi Module, QCN9074-0
WMX7406-I	802.11ax, 4x4, 5G, Enterprise WiFi Module, I-Grade, QCN9074-1 (TBD)

10.2 Accessories (TBD)

Part Number	Description
ATD6251	Dipole Antenna 2dBi 2.4GHz/5GHz
ATD6351	Dipole Antenna 3dBi 2.4GHz/5GHz
ATD6551	Dipole Antenna 5dBi 2.4GHz/5GHz
AC11501	Cable IPEX to SMA, 150mm