


AC/DC Converter

LHE Series			LDE Series	LM Series	LS Series	LI Series	
Standard package	Low power consumption		Compact size	Enclosed	DIY type	DIN-Rail package	
LHE(05-60)-20B  5/10/15/20/25/40/60 Watts 85-264VAC 3000/4000VAC Isolation - Single output	LHE(05-20)-20A/C/D  5/10/15/20 Watts 85-264VAC/100-370VDC 4000VAC Isolation - Multiple outputs	LH15/25-20BxxMU  15/25 Watts 85-264VAC/100-370VDC 4000VAC Isolation - Meet EN60601-1/ANSI/AAMI ES60601-1(2"MOFF) Standards	LDE(03-20)-20B  3/5/6/10/15/20 Watts 85-264VAC/100-370VDC 4000VAC Isolation	LM(35-350)-20B  85-264VAC Input 35/50/75/100/150/200/350 Watts - Single output - Isolation up to 4000VAC	LS01/03/05-15B LS05/08/10-13B  1/3/5/8/10 Watts 85-305VAC/85-264VAC 3000VAC Isolation - Efficiency up to 79%	LI240-10B  240 Watts 3000VAC Isolation - Remote on/off - Active PFC	
LH05/20-13B  5/20 Watts 80-305VAC/100-430VDC 3000VAC	LHE(10-40)-23B  10/15/25/40 Watts 80-305VAC/100-430VDC 4000VAC			LDE03/05-20BxxW  3/5 Watts 85-264VAC/100-370VDC 4000VAC Isolation	LM(35-350)-22B  165-264VAC Input 35/50/75/100/150/200/350 Watts - Single output - Isolation up to 4000VAC	Three phase AC/DC power supply LS03-16B LS05-26B  3/5 Watts 90-528VAC/100-745VDC 4000VAC Isolation - Output short circuit protection	LI(30-100)-20BxxPR2 LI120-20BxxR2  30/60/100/120 Watts 4000VAC Isolation 85(90)-264VAC
			LDE02/05/10-23B  2/5/10 Watts 85-305VAC/120-430VDC 4000VAC Isolation	LM(35-100)-10C/D  85-264VAC Input 35/50/75/100 Watts - Dual/Triple outputs 3000VAC Isolation	LSC15-26M  15 Watts 45-528VAC/65-745VDC 4000VAC Isolation	LO Series Open frame LO(03-65)-10B  3/5/15/30/45/65 Watts 85-264VAC 3000VAC Isolation	

Transceiver Module

Transceiver Module With built in isolated DC/DC Converter	
CAN TD321/521DCAN TD321/521DCANH  110 Nodes - Single output - Rate: 5K-1Mbps, 40K-1Mbps - TDx21DCANx: Two-port isolation (3000VDC) - TDx22DCAN: Two-port isolation (2500VDC)/Channel isolation (1500VDC)	RS485 TD321/521D485 TD321/521D485H(-A/E)  64-256 Node - Single output - Rate: 0-19.2Kbps/0-500Kbps/0-200Kbps options - Two-port isolation 3000VDC (input and output are mutually isolated)
TD301/501MCANFD  110 Nodes - Single output - Rate: 40K-5Mbps - Compact size	TD321/521S485  64 Nodes - Compact size, SMD Package - Rate: 0-19.2kbps 2500/3000VDC Isolation
TD301/501CANHE  110 Nodes - Single output - Rate: 20K-1Mbps - High surge protective type	TD322/522D485H-A  32 Nodes - Dual outputs - Rate: 0-120Kbps
TD321/521SCAN  110 Nodes - Compact size, SMD package - Rate: 5K-1Mbps 3000VDC Isolation	TD331/531S485 TD331/531S485H(-A/E)  - Small SMD12 size - Rate: up to 500Kbps
TD322/522DCAN  110 Nodes - Dual outputs - Rate: 40K-1Mbps	RS232 TD531/331S232H  - Small SMD12 size - Rate: 115200bps - Meet EIA/TIA-232-F standard
TD331/531SCANH/FD  - Small SMD12 size - Rate: 5Mbps 110 Nodes	

AC/DC converter Integrated CAN/485

TLA03/05-03KCAN


- 110 Nodes
- 4000VAC Isolation
- 85-305VAC/100-430VDC
- Rate up to 1Mbps
- Rate: 5K-1Mbps

TLA03/05-03K485


- 128 Nodes
- 4000VAC Isolation
- 85-305VAC/100-430VDC
- Rate up to 500kbps
- Rate: 0-500Kbps

IGBT Driver

IGBT Driver

QC962-8A


- Built-in high CMRR opto-coupler (CMRR: Typ:30kV/μs, Min:15kV/μs)
- High isolation(3750VRMS/min)
- Short-circuit and output fault function

QP12W08S-37(A)


- Built-in DC/DC isolation power supply
- Isolation:3750VAC
- Switching frequency up to 20kHz
- Short-circuit and output fault function

White Goods Power Supply

LD03-20BxxWG


- 3 Watts
- 4000VAC Isolation
- 0.2W Stand-by power consumption
- EN60335 approved

LO15/30-10B


- 15/30 Watts
- 85-264VAC
- 3000VAC Isolation
- Meet requirements of White Goods

3-200W Wide Input Voltage DC/DC Converter R3 Series

High performance at an affordable price

-  Efficiency up to 94%
-  2:1/4:1 Wide input range
-  Stand-by power consumption as low as 0.1W
-  Isolation: 1500/2250/3000/6000VDC



Recommended

For more information, please visit www.mornsun-power.com